

Volta: the All-In.

TECHNICS

TECHNICAL DATA

Height	2580 mm
Width	1500 mm
Length	2865 mm
Weight	420 kg
Power supply	230 VAC
Power consumption	0,75/1Kw



TOP NOTCH WITHOUT COMPROMISE

Time to time, the purchase of a pallet wrapper can be a challenging task, especially if you do not have detailed knowledge of your production needs, or if you don't have a long-term knowledge of your future requirements (i.e. the future possibility of the need to wrap taller, black coloured or very different-shaped pallets that may need to be wrapped differently).

EvoPac Volta allows for this need for flexibility in a brand new premium system.

The machine is equipped as standard with a 2500 mm wrapping height and a super sensitive photocell for background suppression, able to detect the most awkward loads. Finally, together with our new "All Shortcuts" (AS) electronic board, you will be able to wrap everything that differs from your standard just by selecting a different button and without the need for a master's degree in engineering.

Totally customizable, with Volta we attempt to simplify even more your end of line process.



Volta: the All-In.

MAIN SPECIFICATIONS IN STANDARD

Maximum height of the pallet: 2500 mm

Loading plate: 1500 mm

Maximum payload: 1200 Kg

Frequency controller for carriage speed management;

Frequency controller for turntable speed management;

Electromagnetic brake for film stretching;

Custom Photocell for automatic pallet height detection;

Safety stop beneath the carriage;

Double belt system for carriage lifting;

6 working cycles;

Double mode – ALL SHORTCUTS – (AS) – Electronic Board:

- Mode 1 – Fast Program recall (up to 6);
- Mode 2 – 1 click access to the most used wrapping parameters:

Table rotation speed (RPM);

Bottom Wraps;

Top Wraps;

Film Tension;

Carriage ascent speed;

Carriage descent speed.

Autodiagnostic;

2 year warranty.

MAIN OPTIONS

Power Pre-stretch carriage;

Power pre-stretch carriage with auto cut off system;

Double motor pre-stretch carriage;

Double motor pre-stretch with auto cut-off system;

Sealing Unit;

Remote control;

Roping system;

Top press;


UP TO 3400 mm ø table's diameter

Custom wrapping height;

2000 Kg payload;

Weighing system;

Pit frame;



IN OPTION: HIGH PERFORMANCE
PPS CARRIAGE



ALL SHORTCUTS (AS) ELECTRONIC
BOARD



TWIN-BELT SAFETY SYSTEM